

SPECIFICATIONS

GETFIT STANDUP Mat™

Overall Mat Thickness: .75"

Surface

Type: Needle-punched polypropylene

Weight: 14 ozs/sy

Cushion

Type: Nitrile Closed Cell Cushion

Thickness: .625"

Density: 5.5 to 7.5 lbx/ft³

Water Absorption: ASTM D 1667- .01 lb/sq ft maximum

Flammability: FMVSS302- 0 Burn (pass)

Temperature Use: ASTM D 1056- Cold Crack: -20 degrees F

High: 200 Degrees intermittent exposure

Backing

Type: 100% Nitrile Rubber (20% Recycled content)

Thickness: .040"

Durometer: 65

Tensil: 1100 PSI

Testing

- Passes Flammability Standard DOC-FF-1-70
- Passes ATTIC Test method 134-1996 Electrostatic Propensity of Carpets:
Maximum Voltage Negative 0.4 KV
- ASTM C1028-96 Static Coefficient of Friction: Dry - .71 Wet = .70

Features and Benefits

- Outstanding Anti-Fatigue qualities.
- Anti-Static, Slip Resistant 100% solution-dyed polypropylene top surface will not fade or rot.
- Closed-cell Nitrile/PVC cushion backing provides long lasting comfort.
- Beveled border remains flexible for the life of the mat and will not crack or curl.
- Closed-cell cushion backing is permanently molded to the Nitrile Rubber surface, providing a comfortable long lasting mat.
- Sizes: 22" x 32", 22" x 50", 22" x 60", 34" x 47"