



**Dura Trax™** is a high performance anti-fatigue floor mat offering the ultimate in comfort and durability for today's industrial environments. Dura Trax™ combines a noticeably softer rubber top surface with a dense sponge backing material using the NoTrax® exclusive UniFusion™ bonding process. In addition, the rubber surface of the mat resists exposure to sparks making it the perfect choice for welding applications.

available Color: Black, Black/Yellow

Test	Test Description	*Results
ASTM C-1028-96	Static Coefficient of Friction	Dry: 0.80
-	Compression Deflection	@ 20 lbs/in <sup>2</sup> : 0.132 @ 40 lbs/in <sup>2</sup> : 0.233
ASTM D-1004-94a-03	Tear Strength	33.0 lbs
ASTM D-2240	Durometer (Shore A)	85
ASTM D-3884	Abrasion Resistance	@ 500 cycles: 0.5% @ 1000 cycles: 0.9%
ASTM D-2859/CPSC FF-170	Surface Flammability/Carpets and Rugs	Pass
ASTM E-648	Critical Radiant Flux	Watts per Cm <sup>2</sup> : 0.68
ASTM D-1894-01	Modified Slip Test: Avg. C.O.F. (Coefficient of Friction)	VCT: 1.84 Painted Concrete: 2.02 Vinyl Flooring: 1.44 Epoxy Painted Concrete: 1.90
ASTM D-903-98	Delamination	2.9 lbs/in

\*All testing of NoTrax® floor matting has been performed by an independent testing laboratory.



Anti-Slip



Anti-Fatigue



Custom



Welding

- **NEW** - Nitrile rubber blend top for added chemical resistance
- Utilizes NoTrax® exclusive UniFusion™ bond
- RedStop™ non-slip backing
- Top made from 100% recycled materials
- Certified by the NFSI (National Floor Safety Institute)
- Thickness: 9/16"
- Stock Sizes: 2' x 3', 3' x 5'
- Roll Sizes: 2' x 75', 3' x 75', 4' x 75'

